

Kalamazoo Speedway's 2016 Outlaw Super Late Model Rules

A Special Safety Note to all drivers: Highly recommended that you have a Snell 2005 or higher rated helmet & all safety equipment being SFI/1 approved.

100 Decibel Noise Limit on all Cars-No exceptions! All exhaust will exit below the car-not out the side of the door.

Tires will be the Hoosier 970. Absolutely No Tire Soaking or Altering the Tire of Any Kind!

LATE MODEL ALLIANCE RULE AMENDMENTS (11-25-15) In an effort to preserve and maintain the Outlaw Late Model class, and with the goal to reduce speeds, track officials from Berlin, Flat Rock, Kalamazoo, the Main Event Series and Toledo have unanimously agreed to the following changes for the 2016 season. Area tracks that still race Outlaw Super Late Models are encouraged to join us on these amendments.

REAR SPOILER: Maximum 6 inches high by 72 inches wide (material); Must be made of flat, clear material with maximum 1 inch rear-facing lip. Maximum 40 inches from ground to top of spoiler. Rear quarter panel height 34 ½ inches MAXIMUM, measured at the base of the rear spoiler.

FRONT NOSE PIECE: No splitters, NO alterations or additions to after-market nose piece anywhere. Nose to be mounted in conventional manner. Factory molded 3 inch lip MAXIMUM. (This measurement will be reduced to 1 inch for the 2017 season). Nose piece will have no more than 1 ½ inches of belly built into face of nose.

All other measurements/rules pertaining to these 2 items remain in effect for the 2016 season.

2016 Body Measurements All body measurements are to include the driver in the car.

- Minimum roof measurement.....38" L x 45" W
- Maximum rear deck lid (base of spoiler to base of the window).....28"
- Maximum width of top of doors.....4"
- Front Overhang –(Tip of nose to center of hub-includes splitter)..... 45"
- Maximum rear bumper height from ground to bottom of bumper.....12"
- Minimum back panel height perpendicular to the ground.....14"
- Minimum window opening.....12" x 22"
- Minimum height from ground to top of roof, measured 10" back.....45"
- Maximum height of spoiler from the ground.....**40"**
- Maximum at widest point.....82"
- Maximum at center of rear axle.....76"
- Maximum total body width at rear of rear quarters.....72"
- Maximum rear overhand center hub to rear at base of spoiler.....46"
- Minimum rear quarter panel distance from ground.....8"
- Maximum track width measured from outside to outside of tire at the bottom of the center of tire – 82", measured with toe plates.
- Spoiler height (deck to top of spoiler – includes thickness of hinge).....**6"**
- Maximum front of roof to base of rear spoiler.....102"

Maximum of 1.5" of body rake and or belly measured anywhere on the body with a straight edge (measured front to back as well as side by side). This would include side to side across the deck lid, hood or nose pc. as well as from the base of the spoiler up to the front tire. The sides of the body must run in a vertical fashion. No "swoop, dip, belly or concaveness" on the side body panels or anywhere else on the body. The wheel flare on the right rear is a maximum of 3", not to extend past the outside edge of the rear tire.

No more than 2" drop is permitted at any point on the roof. Hood and rear deck lid must be removable and securely fastened down in 4 corners by hood pins or hinges at all time that car is on the track. Hood scoops are allowed (maximum height of 4") in stock height position. No ram air induction. Rear deck lid must be a maximum of 28" from the base of the rear window to the base of the spoiler. The deck lid must be removable or have an access panel minimum of 12" x 12". The rear deck lid drop or "belly" may have a maximum of a 1" drop, checked from side to side of rear quarter panels. The back panel must be a minimum of 14" perpendicular to the ground, fully enclosed. No aluminum or composite bumpers, only steel is allowed. No aluminum door bar assemblies or jacking posts (outside of roll cage) or rub rails. No carbon fiber body components will be permitted, except of the roof.

REAR SPOILER: 6" high x 72" wide (material), made of clear material. Bracing may be from front or rear. For the front bracing, there are a maximum of 3 supports with a maximum of 3/4" round tubing only. Rear bracing must be inset from the sides of the quarter panel a minimum of 3" on both sides. Maximum of 1" rear facing lips only on rear spoiler. Maximum height of 40" from the ground to the top of the spoiler. The right rear quarter panel and rear spoiler must be a minimum of 3" in from the outside right rear tire.

WINDSHIELD AND REAR GLASS: A full front windshield is required. The rear glass may be any continuous elliptical shape resembling a stock design. No tear drop style rear windows. No concave windows. Windows must remain flat in the center. Rear window must have enough bracing in center to keep window from deflecting. Vertical rear window brace is required, placed in the center of the window.

BODY WIDTH: Maximum of 82" at the widest point, steadily decreasing in width to a maximum of 76" at the center of the rear axle and then tapering to a maximum of 72" at the rear spoiler. The sides of the body must run in a vertical fashion. No "swoop" in body panels. No Fender/Wheel flair can extend out past the outer face of rear tires & can't extend beyond the rear of the Tire. The wheel flair on the right rear is a maximum of 3".

SIDE WINDOW OPENINGS: Side window openings are a minimum of 12" high x 22" wide. There are to be no add-on pieces in the window area and no boxing in the window openings.

SHELF: 4" maximum, measured from the front windshield post back to the front of C pillar plus 1" maximum side body radius. C pillar may taper inward no more than 9" from the edge of the body, at a point 52" forward of the base of the rear spoiler. C pillar is to be made of aluminum in a shape resembling the body style of the car's nosepiece and may not be concave in any direction.

FRONT NOSE PIECE: **No splitters, NO alterations or additions to after-market nose piece anywhere. Nose to be mounted in conventional manner. Factory molded 3 inch lip MAXIMUM. (This measurement will be reduced to 1 inch for the 2017 season). Nose piece will have no more than 1 1/2 inches of belly built into face of nose.** The nosepiece flare must be flush with the top of the fender and not have any more that 1.5" of belly in the hood from side to side of the wheel flairs. The nosepiece will have no more than a 1.5" of belly built into the face of the nose. Any nosepiece flattened out or laid back too far will be subject to a 50-100lb penalty; subject to the official's discretion. No nose panning of any kind.

Rear Bumper: Must be a maximum of 12" from the ground to the bottom of the bumper.

No Verticals of any kind: 1" maximum lip along the bottom of the door/quarter panel/skirt

Specifically not allowed: Panning under the sides or rear of car - any louvers or vents in the fenders, doors, or quarters, titanium or carbon fiber rotors – Slipper Clutches – Verticals or lips on the nose pc – Aluminum bumpers or right side door bars. Lead Ballast Only-No other type of Ballast!

WHEEL BASE: Minimum of 101".

TRACK WIDTH: 82" – max, front and rear. This will be measured before and after the race. Will be checked with toe

plates at bulge at the bottom of the tire.

WEIGHT: 2700 pounds before qualifying and before race. 60% left before qualifying and after race.

ENGINE: Any V-8 steel block, (no aluminum blocks). Must be 4" set back from #1 plug.

CARB: Any 4-barrel, 2- return springs.

EXHAUST: Mufflers are mandatory. Max 98-100 decibel.

BRAKES: Must have 4 wheel brakes in working order.

FUEL CELL: 8" minimum at lowest point or must be fully above the rear frame rails. No electric fuel pumps. Fuel cell must be mounted behind rear end inside tires.

FUEL: Racing gas only. No nitrous-alcohol-methanol.

WHEELS: 10" steel only.

Raceceiver's are Mandatory

SUSPENSION: There are to be no independent rear suspension, NO **cockpit adjustments inside of the car besides brake bias** (including but not limited to shocks, sway bar, panhard bars, etc.)

SAFETY EQUIPMENT: A head and neck restraint system is highly recommended. The following are mandatory:

- You must have a window net.
- You must have a 5-point seat belt assembly with a 3" minimum lap belt Maximum two seasons old.
- 5 pound fire suppression system is recommended.
- Racing seats must be aluminum. Full or partial containment seats are recommended

No Mirrors of any kind – No Radios of any kind – No Traction Control of any Kind. Kalamazoo Speedway will have the option at any time to "Confiscate & Switch Out" your MSD Box with a new one. Any driver that refuses to trade their MSD Box will forfeit all points & money for that entire event.

2"x 3" square tubing required for center section. 1 ¾ x .090 4 post cage is recommended.

A Special Safety Note to all drivers: Highly recommended that you have a Snell 2005 or higher rated helmet & all safety equipment being SFI/1 approved.

Contact the speedway office (269-692-2423) or on line at gary@kalamazoospeedway.com for any questions on the rules.