

Kalamazoo Speedway 2017 Flip Flop Cyber Stock Rules

100 Decibel Noise Limit on all Cars-No Exceptions! All cars will have working Mufflers (regardless how long you have run without them) & all exhaust will exit below the car.

A Special Safety Note to all drivers: It is your responsibility to look over and upgrade all of your personal safety equipment. A full containment seat, a head & neck restraint, a fuel cell with all of the proper check valves in place, a new fire suit including the proper under garments, gloves, socks & shoes that are all to the highest of safety ratings. Highly recommended that all safety equipment get upgraded to a Snell 2015 rating and be SFI/1 approved. All safety rules apply. Refer to the General Rules for 2017 before starting on your car.

Kalamazoo Speedway continues to maintain a true entry level class that will be fun for your entire family, will be relatively inexpensive and will introduce new racers into the great sport of short track racing. If the track management deems that your car and or the driver is too advanced for this entry level class, you will quickly be moved up to the Outlaw Cyber Stock class!!

All cars will be required to run a **Raceceiver** in 2017. This is a one way radio that each driver wears that allows our scoring officials to have communication with you out on the track. This is a safety feature for all drivers as well as a tool for the track to be able to speed up the show. These are available at Lane Automotive for approx. \$135 for the complete set up.

Safety Rules will be strongly enforced in this class. You will be required to have a full fire suit as well as a Snell approved Racing Helmet with approved racing gloves. A 4 or 5 point racing harness, a good quality window net with a quick release latch, and adequate roll bar padding will be required. Racing shoes, a head & neck restraint, and an aluminum racing seat are all highly recommended. Call us at the speedway office (269-692-2423) and we will help you better understand any of your required safety equipment. We will cover the complete safety requirements, below in the rules section.

All Flip Flop Cyber Stocks will be 6 cylinder FWD car with an automatic transmission or a 4 cylinder FWD car with an automatic or manual transmission. No convertibles, 2 seat coupes, trucks or super or turbo charged cars will be allowed. These vehicles will remain stock, in their original form and shape. No alterations will be made to your cars, unless it is stated that you may do so.

Base Weight to be 2600 lbs. which includes the driver race ready * Manual Tranny Add 75 lbs. *

Very few cars will have a problem hitting this weight - however to keep an equal balanced class of cars, this minimal weight is a must! Any cars that need to add weight will have to add lead ballast above the floor board only on the right side of the car. No Lead added below the floorboard. All lead must all be mounted secure and safe with ½” bolts & flat washers & will be painted white. All lead mounting will be subject to the tech official's discretions. **And as our rules clearly state, if you have a car and or the talent that is beyond the majority of the cars & drivers in this beginner's class, you will be quickly be graduated up to the Outlaw Cyber Class!**

Complete Stock Bodies – There will be NO Gutting or stripping of any metal inner body panels unless the roll cage bars go all the way out to the door skin. Minor gutting of the non cock pit body parts are OK. **If your car is a four door, the driver's side window/door post between the front & back door can be removed for roll bar clearance and added room to exit & enter the car.**

All exterior body panels will remain stock front to rear.

- There will be no rear or side windows of any kind made out of any material. Any patch work on the interior or exterior of the car will have steel or aluminum patches. Make sure firewall or floor board holes are all patched over well 100%! All patches will be riveted or welded-**there will be no sheet metal or self-taping screws.**
- The original windshield may remain as is, but a full Lexan windshield is highly recommended. All other glass must be removed 100%. All cars will run a full windshield.
- All mirrors, upholstery, insulation inside & under the hood, carpet, tail lights & headlights, all loose trim on the exterior of the body, trailer hitches, and aftermarket add-ons must be removed from the car. Any material burnable in the driver's cockpit area must be removed.

- The original hood & trunk latches must be removed and replaced with a quick release hood pin system. Any car with a hatchback can weld or bolt your hatchback solid or remove the hatchback completely.
- All holes in the floorboard and front firewall must be covered securely with sheet metal.
- Both front & rear bumpers must be strapped or chained to the frame, to prevent dragging. When you remove the vinyl covering on your dashboard, you may cover up the “ugly stuff” with a piece of aluminum or sheet metal. Rub rails OK-securely mounted with carriage bolts & smooth ends.
- A homemade steel bumper may be used as the foam or aluminum bumpers smash down. No heavy tubing or channel. Nothing over 1/8” thickness and 4” tall. This is only being implemented to save you time & money of buying OEM bumpers.....if you add too much support for your bumpers, you will be cutting them off!
- There will be no gutting of any interior or exterior panels, except for making room for the door bars
- Make sure all loose glass or material inside of the body panels are vacuumed out good. All loose rust flakes or trim must be removed from your cars. Use a sledgehammer on your bumpers to knock off all of the loose material on the bottom side of your car.
- Before your car will be allowed on the track, make sure the cockpit area as well as the trunk area is clean & vacuumed out 100%!

Steering & Suspension – All steering and suspension will remain stock with no modifications – front to rear & side-to-side. You will be allowed to have no more than 1” of camber on the front tires and no more than 1/2” on the rear tires, which will be measured with a 24” carpenter’s square. Your wheel base will remain within 1/4” side to side (rear steer). You may have a quick release steering wheel for safety, but will have the complete stock steering assembly. Your brake and gas pedal will remain stock, but you can have a toe clip for a throttle return strap. Struts may be taken off for inspection at any time during that day’s event. No cutting, shortening, heating or stretching of the springs and springs must be stock for that make of car. **All struts & springs will remain Stock Stock Stock!! All cars must bounce freely up & down.**

Engines & Exhaust – All cars must start with the stock ignition key or a simple push button/toggle switch. All of the stock wiring to your car will remain intact. Your engines and transmissions are to remain stock - we will implement a claimer rule on these cars if needed, so don’t throw a bunch of money into your Flip Flop Cyber Stock! A stock style exhaust system complete with a muffler that exits behind the driver’s seat will be mandatory – 2” maximum OD size – catalytic converter not needed. Absolutely no Antifreeze is allowed!


Gas Tanks & Batteries – A stock gas tank in its stock location is required. Double check the gas lines and the tank straps, replace them if they are worn. All Cars must have shut off switch next to driver window which can easily be reached from the outside of the car.

Tires- We will be racing on junk yard stock tires only. There will be no Z rated, bias ply, trailer or recap tires allowed. Single ply sidewall DOT Radial Tires Only!! No New Goodyear Triple Tread tires or high dollar equivalent tires will be allowed. Any **55, 60, 65, 70, 75, or 80 series radial tire 165-215.** Minimum tread wear rating of 300 - Tread wear rating must be visible on outside of tire. All 4 wheels must have the same size tire, no mixing of sizes. Don’t look for a trick or special tire.....KS has the right to reject any tire to race on!

Wheels - Steel wheels only, stock for that year, make and model. **Safety wheel OK** (optional) on right front. Safety wheel must comply with measurements on drawing. A or B Measurement will be close to 3”.

- A= 3” maximum
- B= 3” minimum
- C= 6” maximum wheel width
- All wheels and tires must be the same size. (Exception RF wheel if using Safety wheel)
- 1” lug nut required when using safety wheel. Wheel studs must extend at least one thread beyond lug nut.

Safety Wheel Measurements



- All wheel weights must be removed from both the inside & outside of all wheels.
- No wheel spacers of any kind.

Front & Rear Bumper Hook-up on all Cars - Due to the length of time trying to find a secure place to hook up a car to the wrecker without damaging the body too much, all cars will be required to have a cable or chain to hook up to, in case of the need to tow your car off the track. You will be allowed to add one pc. of 1 3/4" x .090 (maximum size) tubing between your frame horns (both front & rear if needed) to have a solid place to attach your chain/cable hook-up. Make sure your tubing is welded solid & that your chain or cable will lift your car up safely & square with the track (not just around one side of the frame horn).

Safety Requirements – Although we are strongly encouraging people to build and work on their own cars, if you have little or no experience putting in a safe roll cage, contact a good welder to help you install a good quality roll cage, your racing seat, and your 5 point safety belts and window net mounts. All Cyber Stocks will have a minimum of a 4 post roll cage. The minimum round or square tubing size is 1 1/2" x .095 thickness, no exhaust tubing or old rusty well pipe allowed. The rollover bar will be behind the driver's head, with the upper halo section constructed to give the driver plenty of head clearance & protection to provide safety in the event of a rollover. All cars will have a minimum of 3 driver's side door bars, as well as a single or an X door bar on the passenger side. A 30" wide by 12" tall by 1/8" thick driver's side doorplate is required on all cars (minimum size). No removing of any interior door panels except for door bar clearance. All doors must be bolted, welded or chained shut. If you are using a stock seat, make sure you have your seat tracks bolted or welded solid. The back of the seat must be secured to the horizontal back bar of your roll cage. An aluminum racing seat is highly recommended. Rear bars will be a maximum of 1 3/4" round or square tubing. The rear bars may extend rearward from the top of the cage behind the driver, angling down to the rear of the trunk area. You may also have 2 bars extending back from the middle section of the back hoop, rearward. No bars may extend through the rear of your trunk area. You may have an X in between your two rear diagonal bars. The rear strut towers may be supported with your back bars, to help keep your strut towers in place. We will be allowing bars to extend through the front firewall, for added leg protection for the driver (See new rule above). These bars may attach to the strut towers, but may not go any farther forward. Front Hoops are going to be allowed for safety as well as keeping the car from bending so easy. 1 1/2" round tubing maximum-no heavy square tubing or channel. You may build your radiator support rather than using the stock core support. Stock bumpers & all front OEM sheet metal are still required.

All cars will be checked for locked front axles. With one side of the car jacked up, either tire must spin freely when the opposite tire is down on the ground.

Bumpers – We will allow you to beef up & secure your bumpers to your frame mounts, with a maximum of 1/8" thick angle iron or flat stock. A homemade steel bumper may be used as the foam or aluminum bumpers smash down. No heavy tubing or channel. Nothing over 1/8" thickness and 4" tall. This is only being implemented to save you the time & money of buying OEM bumpers.....if you add too much support for your bumpers, you will be cutting them off! You may add one pc. of 1 3/4" x .090 (maximum size) tubing between your frame horns (both front & rear) to give you a solid place to attach your chain/cable hook-up. You may attach standard hardware cloth in front of your radiator, but no expanded steel or equivalent will be allowed.

This is an entry level class for entry level drivers. Kalamazoo Speedway will have the option of moving a said driver up to the Outlaw Cyber's if their performance supersedes the majority of the other drivers in this class. Cheap Cars.....Great Fun for the Whole Family.....Learn about Racing at the Zoo!!

Contact the Speedway Office at 269-692-2423 or at gary@klamazoospeedway.com with any questions you have on the eligibility of the car or any questions you have on the rules.