

TAX DAY KRASH & BASH

APRIL 15, 2023

Drivers (including crew if applicable) must sign a waiver to participate in any event.

Drivers must complete a Driver Information Form.

Drivers must complete and sign a W-4 or W-9 form to be paid (unless one is on file for 2023).

Payout will be by check the night of the event.

All drivers (including crew if applicable) must purchase a pit pass.

Adult pit passes are \$35; Junior pit passes (12 and under) are \$15.








Drivers must be at least 14 years old.

(Drivers competing only in the Spectator Drags must purchase a general admission ticket; no pit pass needed.)

All participants, except Spectator Drag vehicles, must go through a tech inspection two hours prior to show time.

Track officials' decisions are final in all instances (eligibility, race outcomes, unsportsmanlike conduct, etc.)

These types of events are designed to be fun for the audience as well as the participants; however, safety always comes first. No one gets hurt.

-  Full face helmet and fire suit tops are required. Driver must provide his/her own helmet.
-  No open toed shoes are allowed in the pit area.
-  Jeans (no cut offs) are required in the absence of a full fire suit.
-  Shoulder and lap belts are required and must be used; a racing harness is highly recommended.
-  Although not required, air bags should be removed.
-  No alcohol, illegal drugs or recreational drugs allowed in the pit area.
-  Driver door hits or head on hits are not permitted. Drivers violating these restrictions will be disqualified.

EVENTS (INCLUDING PAYOUT)

Spectator Drags
Trailer Race
Stacker Cars
Tough Truck/SUV Contest
Gut & Go Mini Enduro
Three-Wide Road Rage Drags

SPECTATOR DRAGS

1. The first 16 cars to register will constitute the field.
2. Street legal cars/vans/trucks are permitted to race in this event. Excluded vehicles include: race cars, cars trailered in, rally cars, etc.
3. Pairs of two will race one lap around the track.
4. The driver who crosses the finish line first advances to the next round.
5. Rounds will continue until two cars remain.
6. The winner will be determined by the best 2 of 3 laps. Inside and outside lanes will be alternated with the winner of a coin toss picking their lane for the first lap.

PAYOUT

\$250 to win. \$100 to runner-up.

TRAILER RACE

Tow Vehicles

1. Most street legal vehicles may be used. No semi's, box trucks or beefed-up full-sized vehicles.
2. If a tow vehicle is deemed inappropriate or unsafe, it will not be permitted on the track. Kalamazoo Speedway has the right to allow or disallow any vehicle.
3. All side glass must be removed or rolled down 100%. Windshield or rear windows are optional.
4. A steel door plate (highly recommended) may be welded or bolted over the driver's side door.
5. The driver's door must be chained or welded shut. It is highly recommended that all doors are chained or welded shut.
6. All tow vehicles must have working brakes. **No dually trucks allowed.**
7. No solid filled tires. DOT highway tires are required.
8. Tow vehicles and trailers must start out the race with no flat tires or bare wheels.
9. No added weight on tow vehicles.
10. No passengers are allowed in the tow vehicle.
11. No changing of drivers is permitted.
12. This is a novelty race; professional trailer race vehicles can sit this one out.

Trailers

1. Tires must be on the outside of the frame rail. Tires may not have any kind of protection surrounding them.
2. Minimum trailer size is **4 feet wide by 8 feet long** (tongue to rear of trailer).
3. The trailer must weigh a minimum of 300 pounds.
4. All trailers must be hauling something significant. No blow up or plastic toys or figurines.
5. A small flatbed trailer must have a full-size appliance securely attached to the trailer.
6. All trailers (campers, pop-ups, boats, utility, flat bed, etc.) must be approved by Speedway officials.
7. Boat motors and excess trash in the back of trailers must be removed.
8. All fuel tanks must be removed.
9. Ball type or hitch pin type hitches are permitted. No gooseneck trailers.
10. No solid filled tires. DOT highway tires are required.

Race Rules/Objectives

1. During the race the objective is to separate the trailer of your competitors from their tow vehicle.
2. Drivers who lose their trailer or object that was secured to the trailer at the start of the race will be disqualified and must exit to the pit area.
3. The trailer axle including the tires (or wheels) must remain attached to the trailer or the driver will be disqualified.
4. No tow vehicle to tow vehicle hits allowed. Tow vehicles may only hit trailers. Vehicle to vehicle hits will result in the driver being disqualified.
5. The race will run 20 laps or until only one vehicle (with intact trailer) remains and crosses the finish line, whichever comes soonest.
6. The number of laps may be increased to one lap per entry if there are more than 20 entries.
7. The driver with the most original and best-looking trailer starts on the pole.

PAYOUT

\$1000 to win - 500 - 300 - 200 - 100 - 75 - 75 - 75 - 75 - 75

STACKER CARS

General Safety Rules

1. A basic 4-point cage is highly recommended.
2. All side glass must be removed or rolled down 100%. Windshield or rear windows are optional.
3. A steel door plate (highly recommended) may be welded or bolted over the driver's side door.
4. All doors must be welded or chained shut.
5. Having a horizontal crush bar from side to side just behind the driver's seat is recommended.
6. Having a vertical crush/rollover bar behind the driver's seat is recommended.
7. If a battery is in the back seat, it must be securely covered and tightly strapped down.

General Construction Guidelines of Bottom Car

1. The bottom car is responsible for gas and braking.
2. Cars must be stock.
3. Front wheel drive compact cars only.
4. NO RACE CARS WILL BE ALLOWED FOR THE BOTTOM CAR.
5. Stock suspension, stock engine and stock transmission. The theme here is STOCK.
6. The bottom car will have no steering components whatsoever.
7. Windshield or safety bars must remain in the vehicles.
8. 7" wide maximum stock or safety wheels. No more than a 3.5" backset on any wheel.
9. Stock DOT radial tires (i.e. any 55, 60, 65, 70, 75 or 80 series radial tire 165-215). No trick, racing or exotic tires. No Z-rated tires. No wheel spacers of any kind. lift or bobcat tires.

General Construction Guidelines for the Top Car

1. The top car will do all steering.
2. The complete body shell from bumper to bumper must remain intact, including the front and rear firewalls.
3. All suspension, engine, K-frame, wheels and tires may be removed.
4. The complete body including the front and rear tail panels, bumpers and the full body between the bumpers is required so the car body up top resembles that of a full car.

The number of laps run will depend on car count.

No 2-way radios or other communication devices are allowed.

PAYOUT

\$400 to win - 250 - 150 - 100

TOUGH TRUCK/SUV CONTEST

General Rules

1. The Tough Truck Contest is a timed obstacle course. This course will be run in the infield as well as on the track. The course design will vary from event to event.
2. All participants must be ready to compete after being signaled by the starter. Failure to do so is possible grounds for disqualification.
3. If a vehicle jumps the start, one restart will be allowed. A second jump start will result in disqualification.
4. Vehicles will have at least two (2) opportunities to compete a lap. If a third opportunity is given, the fastest of the three (3) laps will be used to determine the winner.
5. A vehicle must go over the obstacle ramps with both front tires.

6. If a vehicle does not meet the obstacle with the two front tires, a 5 second penalty will be assessed and added to the vehicle's lap time.
7. If vehicle misses the ramp completely, a 10 second penalty will be assessed.
8. If a vehicle touches a marker or barrier, a 5 second penalty will be assessed and added to the vehicle's lap time.
9. All vehicles will be timed by track scorers, with each vehicle's lap time posted on the scoring tower.
10. A participant is racing the clock; no other vehicle will be on the course at the same time. The fastest lap will determine the winner.
11. Speedway officials will determine which classification a vehicle will compete. A vehicle may only compete in one class.

Stock Class Specs

1. All vehicles will be an ordinary two or four-wheel drive stock pickup or SUV.
2. Stock frame & suspension is required.
3. The truck body must be firmly attached to chassis. Loose objects must be removed from interior of the vehicle. No garbage, spare tires, etc., is allowed in the back of the truck or hatch.
4. All spare tires mounted below the truck beds must be removed.
5. Each vehicle's battery must be securely held in place.
6. All vehicles must have exhaust.
7. All vehicle must have working brakes.
8. All vehicles must have the side windows removed or lowered all the way down.
9. **All vehicles must have a skid plate of a minimum 1/8" thick aluminum or steel, that goes from below the front bumper down to the engine crossmember. Skid plates will be required to participate.**
10. Single shock on all four corners: OEM aftermarket shocks are allowed.
11. A lift kit (4" or smaller) is allowed. Oversized tires (up to 33") are allowed.
12. A full body is required. No modified buggies. Front grills or tailgates are optional.
13. Any vehicle with a soft top (Jeep Wrangler) must have a roll cage.
14. A full fire protection racing suit, racing gloves and head & neck protection is highly recommended.
15. All vehicles competing must have a clear and legible number on both sides.

Modified Class Specs

A class for modified trucks & SUVs will be added beginning with the June 24 Night of Destruction.

PAYOUT

\$1000 to win - 500 - 300 - 200 - 100 - 75 - 75 - 75 - 75 - 75

GUT & GO MINI ENDURO (35 LAPS)

General Rules

1. Four or six cylinder, front wheel drive, factory fuel injection, complete stock body and complete stock frame from front to rear. All exterior body panels will remain stock front to rear.
2. No alterations will be made unless the rules expressly state alterations are permissible.
3. No convertibles, 2 seat coupes, trucks or super or turbo charged cars are allowed.
4. Drivers may secure bumpers to frame mounts with a maximum of 1/8" thick angle iron or flat stock. No heavy tubing or channel. Nothing over 1/8" thick and 4" tall. This is permissible to save teams time and the cost of purchasing OEM bumpers. Adding too much bumper support will result in the team cutting them off. Allowable is adding one piece of 1.75" x .090 (maximum size) tubing between frame horns (both front and rear) to provide a solid place to attach the chain/cable

hook-up. Standard hardware cloth may be attached in front of the radiator, but no expanded steel or equivalent is allowed.

5. Both front and rear bumpers must be strapped or chained to the frame to prevent dragging. When removing the vinyl covering on the dashboard, the "ugly stuff" may be covered up with a piece of aluminum or sheet metal. Rub rails are allowable when securely mounted with carriage bolts and smooth ends.
6. Any patch work on the exterior of the car will have steel or aluminum patches. All sheet metal will be riveted or welded; no sheet metal or self-tapping screws.

Engines, Fuel Tanks and Exhaust

1. Unaltered stock ECM computers. No aftermarket computer chips.
2. Cars will use OEM transmissions and engines that match the make of the car (i.e., Chevy to Chevy; Ford to Ford; Honda to Honda, etc.)
3. All cars must start with the stock ignition key or a simple push button/toggle switch. All of the stock wiring to the car will remain intact. Engines and transmissions are to remain stock.
4. Stock style exhaust with a working muffler.

Wheels and Tires

1. 7" wide Maximum Stock or safety wheels. No more than a 3.5" backset on any wheel.
2. Stock DOT Radial Tires. No trick or exotic tires. No Z Rated Tires
3. Any 55, 60, 65, 70, 75 or 80 series radial tire 165-215. Minimum tread wear rating of 300. Tread wear rating must be visible on outside of tire. All 4 wheels must have the same size tire, no mixing of sizes. The track has the right to reject any tire.
4. No wheel spacers of any kind.

Gas Tanks and Batteries

A racing fuel cell or a stock gas tank in good condition and in its stock location is required. Double check the gas lines and the tank straps, replace them if they are worn. All cars must have a shut off switch next to driver window which can easily be reached from the outside of the car. Batteries can remain in stock location or can be moved to the cockpit behind the driver. Any cockpit mounted battery must be 100% covered and secured.

Cockpit

1. There will be no gutting or stripping of any metal inner body panels unless the roll cage bars go all the way out to the door skin. Minor gutting of the non-cockpit body parts is allowable. For four door cars, the driver's side window/door post between the front and back door may be removed for roll bar clearance and added room to exit and enter the car.
2. The original windshield may remain as is; however, a full Lexan windshield is highly recommended. All other glass must be removed. All cars will run a minimum of a 30" wide windshield positioned over the driver.

Steering and Suspension

1. All steering and suspension will remain stock with no modifications, front to rear and side-to-side. No more than 1.5" of camber on the front tires and no more than 1/2" on the rear tires (measured with a 24" carpenters square).
2. The wheelbase will remain within a half inch from side to side (rear steer).
3. Drivers may have a quick release steering wheel for safety. The complete stock steering assembly must remain.
4. Brake and gas pedals will remain stock. A toe clip on the gas pedal is highly recommended.

5. Struts may be taken off for inspection at any time during the event. No cutting, shortening, heating or stretching of the springs. Springs and struts must be stock for the car's make, model and year. **All cars must bounce freely up and down.**
6. All cars will be checked for locked front axles. With one side of the car jacked up, either tire must spin freely when the opposite tire is on the ground.

Safety

1. All Enduro cars are strongly recommended to have a minimum of a 4 post roll cage. The minimum round or square tubing size is 1.5" x .095" thick; no exhaust tubing or old rusty well pipe allowed.
2. Full face helmet and fire suit top will be the minimal requirements.
3. Full jeans, socks & shoes (no sandals or open toes shoes) required.
4. Shoulder and lap belts are required; racing harness is highly recommended.
5. A latching window net is strongly recommended in all cars.
6. It is highly suggested that, at minimum, all cars have a steel door plate over the driver's door along with a horizontal bar, channel or tube welded securely between the two uprights of the cars main shell just behind the driver's seat. Drivers will then have a safe secure place to attach the back of your seat as well as a good place to attach a set of aftermarket shoulder harnesses.
7. Air bags must be removed.
8. When using a stock seat, make sure the seat tracks are solidly bolted or welded.
 - a. Rear bars will be a maximum of 1.50" round or square tubing. The rear support bars may extend rearward from the top of the cage behind the driver, angling down to the rear of the trunk area.
 - b. Two bars may extend back from the middle section of the back hoop rearward. No bars may extend through the rear of the trunk area. Drivers may have an X between the two rear diagonal bars. The rear strut towers may be supported with the back bars to help keep strut towers in place. Bars are allowed to extend through the front firewall for added leg protection for the driver. These bars may attach to the strut towers, but may not go any further forward. Front hoops are allowed for safety. 1.5" round tubing maximum. No heavy square tubing or channel.
 - c. Radiator support may be built using light weight steel rather than using the stock core support.
 - d. Stock bumpers and all front OEM sheet metal are required.
9. The original hood and trunk latches must be removed and replaced with a quick release hood pin system. Any hatchback may be removed entirely or must be solidly welded or bolted shut.
10. All holes in the floorboard and front firewall must be covered securely with sheet metal. All sheet metal will be riveted or welded; no sheet metal or self-tapping screws.
11. Carefully vacuum all loose glass or material from the interior of the body panels. All loose rust flakes or trim must be removed from cars. Use a sledgehammer on bumpers to knock off the loose material from the undercarriage.
12. The cockpit and trunk areas must be clean and vacuumed before a car is allowed on the track.

PAYOUT

\$1000 to win - 500 - 300 - 200 - 100 - 75 - 75 - 75 - 75 - 75

THREE-WIDE ROAD RAGE DRAGS

1. Vehicles must be front wheel drive, 4 or 6 cylinder subcompacts, mini vans, small SUV's, or small pick-ups (no full size trucks or SUV's permitted).
2. The event is limited to the first 18 drivers to sign up.
3. Three vehicles start side by side in Turn 1.
4. Vehicles race down the front stretch toward a large tire in Turn 4.
5. Upon reaching the tire, race (in either direction) around the tire and then back to the finish line.
6. The first driver to the finish line advances to the next round.
7. The event continues until all but one car has been eliminated.

PAYOUT

\$250 to win - 125 - 100

To sign up for any event, write gary@kalamazoospeedway.com or call (269) 355-4628. All participants must complete a Driver Information Form. **Please complete the form and bring it with you to the event.** Forms are available on the Kalamazoo Speedway website under the Krash & Bash post.